

# Technical Bulletin



---

Model(s)	Year	Eng. Code	Trans. Code	VIN Range From	VIN Range To
All	2000 > 2010	All	All	All	All

## Condition

50 07 02 Feb. 22, 2007, 2014370, Supersedes Technical Bulletin Group 50 number 99-03 dated September 16, 1999 due to inclusion into ElsaWeb and Content.

Paint Finish, Reducing Swirl Marks and Fine Scratches

New vehicles (prior to Retail Delivery) with swirl marks and or fine scratches from polishing or cleaning.

## Technical Background

Not applicable.

## Production Solution

Not applicable.

## Service

Finish can be significantly improved without the use of harsh polishing compounds and high speed buffing.

Use the following steps IN SEQUENCE to insure the greatest margin of paint surface improvement:

 <b>WARNING</b>
Always read and follow manufacturer Cautions and Warnings regarding use of product.

- Wash vehicle using a mild automotive detergent.
- Hand dry vehicle.



Tip:

**DO NOT wash or dry vehicle in direct sunlight. Rapid water/soap solution evaporation may form "water spots" on the paint surface.**

- Hand apply 3M Perfect-It™ Paste Wax (3M Part No. 39526) or equivalent (follow manufacturer instructions regarding use of product).

# Technical Bulletin



- Apply wax to panel sized area (door, fender etc.) using a firm circular motion.

After wax dries to a hazy finish:

- Polish by hand using a 3M Perfect-It™ Detailing Cloth (3M Part No. 39016) or a clean dry terry cloth towel.

## Warranty

Information only.

## Required Parts and Tools

Description	Tool No:	Quantity
3M Perfect-It™ Paste Wax	3M 39526*	1
3M Perfect-It™ Detailing Cloth	3M 39016*	1

\* Call Volkswagen Tools and Equipment Program (EQS), which is Equipment Solutions, at 1-800-892-9650 for product.